



The Delphion Integrated View

Buy Now: [More choices...](#)

Tools: Add to Work File: [Create new W](#)

View: [INPADOC](#) | Jump to: [Top](#) ☒ Go to: [Derwent...](#)

☒ [Em](#)

Title: JP9052747A2: IRRITANT FOR BLENDED CEMENT AND BLENDED C

Country: JP Japan

Kind: A

Inventor: MORIOKA MINORU;
HOKARI TAMOTSU;
ISHIDA TSUMORU;
SAKAI ETSURO;

Assignee: DENKI KAGAKU KOGYO KK
[News, Profiles, Stocks and More about this company](#)

Published / Filed: Feb. 25, 1997 / Aug. 17, 1995

Application JP1995000209463

Number:

IPC Code: [C04B 22/14](#); [C04B 7/153](#); [C04B 7/24](#); [C04B 7/26](#); [C04B 22/06](#); [C04B 28/08](#); [C04B 28/08](#)
[C04B 103/14](#);

ECLA Code: [C04B7/32B](#); [C04B22/14G](#);

Priority Number: Aug. 17, 1995 JP1995000209463

Abstract:


PROBLEM TO BE SOLVED: To produce an irritant for a blended cement usable mainly in a civil engineering construction industry and capable of preparing a blended cement composition having good initial strength manifesting property and a large neutralization suppressing effect.

SOLUTION: The irritant for the blended cement is formed by heat treating a blend containing a CaO starting material, an Al₂O₃ starting material and a CaSO₄ starting material and composed of a mineral group with a free lime, hauynite and anhydrous gypsum as an active principle and has =3,000cm²/g Blaine value and =20µm average grain size, and has CaO/Al₂O₃mol. ratio of 7.5-18 and CaSO₄/Al₂O₃mol. ratio of 1.6-4. The blended cement composition is formed from cement and this irritant for the blended cement.

COPYRIGHT: (C)1997,JPO

Family: None

Other Abstract CHEMABS 126(18)241736V CAN126(18)241736V DERABS C97-197131 DERC97-197
Info:



[Nominate this fo](#)